



Connectable with various ECR system



easy to controll



adjustable view angle of indicator

PDI INDICATOR

Check-out scale Indicator

- Suitable to use in narrow place as simple indicator
- Connectable with various ECR & POS system
- Offering suitable solution to various shop such as supermarket and general store etc



CAS

PDI | Check-out scale Indicator

Adjustable view angle of indicator



The user can view weight in various angle with adjustment of view angle of indicator

SPECIFICATIONS

Model	PDI	
Applied voltage for load cell	DC 5V(350Ω maximum 8 possible connections)	
Zeroing range	0~2 mV/V	
Input sensitivity	0.5 uV/D (OIML,)Nteq, KS	
	0.5 uV/D (Non OIML,)Nteq, KS	
A/D internal resolution	1/520,000	
A/D external resolution	1/10,000 (NTEP,)OIML, KS	
	1/20,000 (Non NTEP,)OIML, KS (Possible with the use of sufficient output at 2mV/V L/C)	
A/D conversion speed	80 rounds/second	
Sign for status	STABLE, NET, ZERO, COM	
Weight display	LCD(6 digit + Sign)	
AC Adapter	AC 100~240 V(DC 12V, 1.25A)	
Operating temperature	-10°C ~ 40°C	
Product size(mm)	141(W) X 101(D) X 382(H)	
Product weight	500g	
Product weight	Standard	COM1(RS-232 Printer & PC Interface)
	Option	USB

FEATURES

- Suitable for the Checkout scale and weighing system
- Easy operations
- Simple and prompt full digital calibration (automatic weight setup at once)
- Weight backup functions
[restoring weight at the power supply On/Off]
- Multiple weights setup functions
[5 point input weight setup]
- Command Mode [ECR Protocol]
- 6 line [basic]/4 line load cell Input

CAS

CAS BLDG., # 440-1, SUNGNAE DONG,
GANGDONG GU, SEOUL, KOREA

TEL_ 82 2 2225 3500

FAX_ 82 2 475 4668

<http://www.globalcas.com>

Specifications are subject to change for improvement without prior notice.

Connectable with various platform

Connectable with various ECR system, POS system and check out scale



OPTIONS

- USB Interface

DIMENSIONS

